

Product Overview

Hydronic Underfloor Heating

ENGINEERING
TOMORROW



Wired Room Controls

Wireless Room Controls



		Danfoss Icon™ Dial 230V	Danfoss Icon™ Display 230V	Danfoss Icon™ Programmable 230V	Danfoss Icon™ Display 24V	Danfoss Icon™ Wireless Dial	Danfoss Icon™ Wireless Display Infrared available
Features	Energy saving						
	Comfort level	 Floor sensor not supported	 Floor sensor not supported	 Floor sensor supported	 Floor sensor supported	 Floor sensor not supported	 Infrared floor sensor supported
	Advanced features				 App control	 Auto balancing	 Supply C° control
	Cooling option						
	Adaptive learning						
	Switchable frames	 Available for in-wall	 Available for in-wall	 Available for in-wall	 Available for in-wall		
	Installation	 On-wall	 In-wall	 On-wall	 In-wall	 On-wall	 On-wall
	Master Controller fit	230V	230V	230V	24V	24V	24V

Product Overview

Hydronic Underfloor Heating

ENGINEERING
TOMORROW




Supply Temperature Controls Mechanical systems



		FHM-C1 Best with 230V system	Midi Shunt Danfoss Icon™ 230V included
Features	Energy saving		
	Prefabrication (ready to go)	 Incl. pump, temp. sensor and fittings	 Incl. pump, temp. sensor, fittings and backplate. Needs only pipe connection. One circuit only
	Plug and play installation		
	Control	Controlled by FTC temp. sensor	Controlled by FTC temp. sensor + Danfoss Icon™ 230V

Basic Manifold

Advanced Manifold



		SSM (without flowmeter)	SSM-F (with flowmeter)
Features	Comfort level		
	Hydronic balancing		
	Pre-setting	+	++
	Integrated end section		